```
# Makefile for prettyp suite
# $Id: Makefile,v 1.3 1999/02/18 00:44:58 elf Exp elf $

# Where to install binaries (BINDIR must exist)
        BINDIR = /usr/local/bin

# Where to install the man-pages (MANDIR must exist)
        MANDIR = /usr/local/man/man1


# Where TeX is installed
        TEXDIR = /usr/local/share

# Where support files that tfontedpr needs will go. If you have a
#   filesystem that is mounted across different architectures, then
#   install these files there (TEXINPUTS will be created if
#   non-existant).
     TEXINPUTS = ${TEXDIR}/texmf/tgrind

# Where the perl interpreter is found
        PERLOC = /usr/local/bin/perl
#       PERLOC = /usr/bin/perl                  # on GNU/Linux

# Where the install program is found
     INSTALLOC = /usr/ucb/install
#    INSTALLOC = /usr/bin/install               # on GNU/Linux

# Compiler and flags
            CC = gcc
        CFLAGS = -g

#-----------------------------------------------------------------
#Don't modify anything past here unless you know what you're doing
.PRECIOUS: distrib

       VERSION =2.0

          SRCS = tfontedpr.c vgrindefs.c regexp.c
          OBJS = tfontedpr.o vgrindefs.o regexp.o
        TARGET = tfontedpr
       SCRIPTS = lang prettyp
      MANIFEST = README ${SRCS} Makefile tgrindmac.tex vgrindefs.5.ps vgrindefs.src tgrind.sh prettyp lang.src tgrind.1 prettyp.1 tfontedpr.1 README.orig tgrind.sty tgrindn.sty GNU ACKNOWLEDGEMENTS

      DEFSFILE = ${TEXINPUTS}/vgrindefs
      MACSFILE = ${TEXINPUTS}/tgrindmac

all: $(TARGET) $(SCRIPTS)                                              all

${TARGET}: ${OBJS}
        ${CC} ${CFLAGS} -o ${TARGET} ${OBJS}

tfontedpr.o: tfontedpr.c
        ${CC} ${CFLAGS} -DDEFSFILE=\"${DEFSFILE}\" \
```

```
	-DMACSFILE=\"${MACSFILE}\" -c tfontedpr.c
```

prettyp

```
prettyp: prettyp.src
	sed "s+@@TEXDIR@@+${TEXDIR}+" < prettyp.src > prettyp
	chmod a+x prettyp
```

lang

```
lang: lang.src
	echo "#!${PERLOC}" > lang
	echo "#THIS FILE WAS GENERATED FROM lang.src -- DO NOT EDIT!" >> lang
	sed -e '1d' <lang.src >> lang
	chmod a+x lang
```

install

```
install: all
	${INSTALLOC} -c ${TARGET} ${BINDIR}/tfontedpr
	${INSTALLOC} -c tgrind.sh ${BINDIR}/tgrind
	${INSTALLOC} -c prettyp ${BINDIR}/prettyp

	${INSTALLOC} -c lang ${BINDIR}/lang

	${INSTALLOC} -d ${TEXINPUTS}
	${INSTALLOC} -c tgrindmac.tex ${TEXINPUTS}/tgrindmac.tex
	${INSTALLOC} -c vgrindefs.src ${DEFSFILE}

	${INSTALLOC} -c tgrind.1 ${MANDIR}
	${INSTALLOC} -c prettyp.1 ${MANDIR}
	${INSTALLOC} -c tfontedpr.1 ${MANDIR}
```

distrib

```
distrib: prettyp-${VERSION}.tar.gz
	@./distrib ${MANIFEST}

prettyp-${VERSION}.tar.gz:
	@echo Building prettyp-${VERSION}.tar.gz...
```

clean

```
clean:
	-rm -f ${SCRIPTS} ${TARGET} ${OBJS} core
```